

View Online at <https://aerobasegroup.com/nsn/5930-00-951-0132>

Thread Class:

2b

Body Style:

Hole mounted

Body Length:

1.880 inches

Body Width:

Between 0.490 inches and 0.550 inches

Body Height:

Between 1.270 inches and 1.330 inches

Unthreaded Mounting Hole Diameter:

0.138 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

115.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

14.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

0.250 amperes resistive dc and 0.100 amperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac

Test Data Document:

81349-mils8805-56 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0