# NSN 5930-00-951-5671

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-951-5671

### **Thread Class:**

2b single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

3.125 inches

#### **Overall Height:**

2.812 inches

#### **Overall Width:**

2.812 inches

#### First Flat Length:

0.875 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

1.125 inches single actuator

## Individual Section Quantity:

5

### Knob Manufacturer Code:

82121

### Knob Manufacturer Part Number:

А

#### Longest Horizontal Distance Between Mounting Centers:

2.297 inches single mounting facility

#### Longest Vertical Distance Between Mounting Centers:

2.297 inches single mounting facility

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### **Throw Quantity:**

1 each section rear

#### Mounting Method:

Threaded hole single mounting facility

#### **Features Provided:**

Actuator knob

### Thready Qty Per Inch (tpi):

24 single mounting facility

## Thread Size:

0.190 inches single mounting facility

# NSN 5930-00-951-5671

Rotary Switch - Page 2 of 2



**Contact Voltage Rating In Volts:** 125.0 ac at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted, threaded hole single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 45.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 10.0 amperes resistive load ac at sea level Style Designator: Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0