NSN 5930-00-951-6451

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-951-6451
Body Style:
Hole mounted
Overall Length:
0.510 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.178 inches and 0.198 inches
Overall Height:
0.470 inches
Overall Width:
0.210 inches
Body Length:
0.510 inches
Body Width:
0.210 inches
Body Height:
Between 0.340 inches and 0.360 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Height:

Between 0.020 inches and 0.040 inches

Actuator Free Position Height:

Between 0.305 inches and 0.335 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

NSN 5930-00-951-6451

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0