## NSN 5930-00-952-4530

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-952-4530

Overall Length:
5.188 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Capillary Tube Length:
120.0 inches
Bulb Length:
3.625 inches
Bulb Diameter:
0.688 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+70.00/+140.00 actuation point degrees fahrenheit and +70.00/+140.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw

## NSN 5930-00-952-4530

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volt
550.0 dc at sea level third voltag
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0