NSN 5930-00-952-8498

Rotary Switch - Page 1 of 2

Thread Class:

Thread Length:

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-952-8498

0.375 inches single mounting facility **Overall Length:** 3.265 inches **Overall Height:** 1.484 inches **Overall Width:** 1.438 inches **Nonturn Device Radius:** 0.438 inches at 12: 00 o'clock **Individual Section Quantity: Knob Manufacturer Code:** 71590 **Knob Manufacturer Part Number:** P-120 **Nonturn Device Type:** Tab at 12: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 12 each section rear **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 6.0 lowest dc voltage rating at sea level **Rotor Through Connection Quantity:** 1 each section **Switch Actuator Indexing Position Quantity:** 12 single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks each section rear

NSN 5930-00-952-8498

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

5.5 amperes resistive load highest dc voltage rating at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0