

View Online at <https://aerobasegroup.com/nsn/5930-00-952-9031>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Overall Length:**

1.250 inches

**Overall Height:**

0.562 inches

**Overall Width:**

0.562 inches

**Body Diameter:**

Between 0.547 inches and 0.577 inches

**Bushing Length:**

Between 0.235 inches and 0.265 inches

**Body Length:**

Between 0.408 inches and 0.438 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.297 inches and 0.327 inches

**Actuator Height:**

Between 0.172 inches and 0.202 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

120.0 ac and 120.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.500 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 15.000 amperes resistive ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

4 screw

**Specification Data:**

96906-ms16712 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0