

View Online at <https://aerobasegroup.com/nsn/5930-00-952-9031>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

1.250 inches

Overall Height:

0.562 inches

Overall Width:

0.562 inches

Body Diameter:

Between 0.547 inches and 0.577 inches

Bushing Length:

Between 0.235 inches and 0.265 inches

Body Length:

Between 0.408 inches and 0.438 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.297 inches and 0.327 inches

Actuator Height:

Between 0.172 inches and 0.202 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

120.0 ac and 120.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 15.000 amperes resistive ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un

Terminal Type And Quantity:

4 screw

Specification Data:

96906-ms16712 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0