

View Online at <https://aerobasegroup.com/nsn/5930-00-953-5369>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion proof and explosion proof and oiltight and watertight

**Body Length:**

1.220 inches

**Body Width:**

0.520 inches

**Body Height:**

1.300 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.500 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.600 inches

**Actuator Free Position Height:**

0.375 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac and 3.300 amperes motor ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0