

View Online at <https://aerobasegroup.com/nsn/5930-00-953-5369>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion proof and explosion proof and oiltight and watertight

Body Length:

1.220 inches

Body Width:

0.520 inches

Body Height:

1.300 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.600 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 2.000 amperes lamp ac and 3.300 amperes motor ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0