NSN 5930-00-954-6672

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-954-6672

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.750 inches
Body Length:
3.660 inches
Body Width:
2.015 inches
Body Height:
2.560 inches
Switch Actuator Quantity:
1
Actuator Length:
1.562 inches
Actuator Style:
Roller arm
Actuator Height:
2.000 inches
Actuator Roller Diameter:
0.718 inches
Actuator Roller Width:
0.281 inches
Actuator Adapter Style:
Roller arm
Housing Height:
2.560 inches
Housing Length:
3.660 inches
Housing Width:
2.015 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.812 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.750 inches
Maximum Voltage Rating In Volts:
125.0 ac and 28.0 dc
Inclosure Type:
Hermetically sealed
Thread Size:
0.190 inches
Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

NSN 5930-00-954-6672

Sensitive Switch - Page 2 of 2

No Fiig: A053a0



Switch Actuating Force:
Between 8.0 ounces and 24.0 ounces
Actuator Movement:
0.219 pretravel inches and 90.0 overtravel degrees and 0.025 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
$25.000 \ \text{amperes}$ resistive dc and 10.000 amperes inductive dc and 1.000 amperes resistive ac
Special Features:
W/mounting bracket
Thread Series Designator:
Unf
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: