NSN 5930-00-955-0154

Pressure Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-955-0154
Longest Horizontal Distance Between Mounting Centers:
0.790 inches
Longest Vertical Distance Between Mounting Centers:
2.812 inches
Pressure Switch Type:
Differential
Mounting Method:
Base
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
1.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Contact Stimulus Rating:
Contact Stimulus Rating: 5.00 actuation point pounds per square inch
Contact Stimulus Rating: 5.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Contact Stimulus Rating: 5.00 actuation point pounds per square inch Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage
Contact Stimulus Rating: 5.00 actuation point pounds per square inch Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Frequency In Hertz:
Contact Stimulus Rating: 5.00 actuation point pounds per square inch Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Frequency In Hertz: 60.0 single voltage
Contact Stimulus Rating: 5.00 actuation point pounds per square inch Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed:
Contact Stimulus Rating: 5.00 actuation point pounds per square inch Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed: Liquid
Contact Stimulus Rating: 5.00 actuation point pounds per square inch Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed: Liquid Shelf Life:
Contact Stimulus Rating: 5.00 actuation point pounds per square inch Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed: Liquid Shelf Life: N/a
Contact Stimulus Rating: 5.00 actuation point pounds per square inch Contact Voltage Rating In Volts: 30.0 dc at sea level second voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed: Liquid Shelf Life: N/a

Fiig:

A048b0