

View Online at <https://aerobasegroup.com/nsn/5930-00-955-1133>

Thread Length:

0.359 inches single mounting facility and 0.391 inches single mounting facility

Overall Length:

Between 1.641 inches and 1.673 inches

Overall Height:

Between 1.484 inches and 1.766 inches

Overall Width:

Between 1.265 inches and 1.328 inches

First Flat Length:

0.390 inches single actuator and 0.422 inches single actuator

Flat Height:

0.212 inches single actuator and 0.234 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.828 inches single actuator and 0.860 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 2: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

240.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0