## NSN 5930-00-955-5373

Push Switch - Page 1 of 2



V	iew Online at https://aerobasegroup.com/nsn/5930-00-955-5373
В	ody Style:
Р	Panel mounted
C	Overall Length:
4	.188 inches
C	Overall Height:
1	.200 inches
C	Overall Width:
0	.960 inches
В	ody Width:
0	.960 inches
В	Sody Height:
1	.200 inches
C	Case Material:
Ν	Metal or plastic
A	ctuator Length:
1	.035 inches
A	ctuator Style:
R	tectangular
A	ctuator Height:
0	.188 inches
A	ctuator Width:
0	.735 inches
A	ctuator Color:
V	Vhite single actuator
II	luminated Actuator Color:
G	Green single actuator and white single actuator
	ctuator Inscription:
	-m mission single actuator
	laximum Voltage Rating In Volts:
	50.0 ac and 30.0 dc
	lounting Surface To Terminal End Distance:
	.000 inches
	nclosure Type:
	fully enclosed
	lounting Method:
Р	Panel

**Features Provided:** 

Full display lens and holding solenoid

**Nonpile-up Contact Arrangement:** 

4 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:** 

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

## NSN 5930-00-955-5373

Push Switch - Page 2 of 2



Precious	Material	∆nd ∣	Location:

Terminal surfaces and contacts silver

**Terminal Type And Quantity:** 

12 turret and 7 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A053a0