

View Online at <https://aerobasegroup.com/nsn/5930-00-955-9847>

**Thread Class:**

2a single mounting facility

**Hazardous Locations/environmental Protection:**

Fungus resistant and humidity resistant and shock resistant and vibration resistant

**Overall Length:**

4.050 inches

**First Flat Length:**

0.740 inches 2nd actuator

**Flat Height:**

0.182 inches 2nd actuator and 0.192 inches 2nd actuator

**Shaft Diameter:**

0.468 inches 1st actuator

**Shaft Length:**

0.800 inches 2nd actuator

**Overall Diameter:**

2.370 inches

**Individual Section Quantity:**

4

**Longest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Operating Temperature Range:**

-75.0/+122.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

4 single section front

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Makes before breaks 2nd section front

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

6.0 amperes resistive load dc at sea level and 6.0 amperes inductive load dc at sea level

**Style Designator:**

Circular wafer, panel mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0