

View Online at <https://aerobasegroup.com/nsn/5930-00-955-9847>

Thread Class:

2a single mounting facility

Hazardous Locations/environmental Protection:

Fungus resistant and humidity resistant and shock resistant and vibration resistant

Overall Length:

4.050 inches

First Flat Length:

0.740 inches 2nd actuator

Flat Height:

0.182 inches 2nd actuator and 0.192 inches 2nd actuator

Shaft Diameter:

0.468 inches 1st actuator

Shaft Length:

0.800 inches 2nd actuator

Overall Diameter:

2.370 inches

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.000 inches single mounting facility

Operating Temperature Range:

-75.0/+122.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

4 single section front

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks 2nd section front

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

6.0 amperes resistive load dc at sea level and 6.0 amperes inductive load dc at sea level

Style Designator:

Circular wafer, panel mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0