## NSN 5930-00-955-9919

**Hazardous Locations/environmental Protection:** 

Pressure Switch - Page 1 of 2

Dustproof

Overall Length: 1.938 inches

**Outside Diameter:** 

Overall Height: 3.375 inches Overall Width:

0.125 inches single connection



View Online at https://aerobasegroup.com/nsn/5930-00-955-9919

1.000 inches					
Body Height:					
1.375 inches					
Pressure Switch Type:					
Gage					
Mounting Method:					
Inlet connection					
Contact Action Stimulus:					
Increase					
Proof Pressure:					
90.00 pounds per square inch					
Thread Size:					
0.125 inches single pressure connection					
Nonpile-up Contact Arrangement:					
1 pole, double throw, one position momentary					
Terminal Type:					
Screw					
Contact Load Current Rating:					
Contact Load Current Rating:					
Contact Load Current Rating: 15.0 amperes resistive load single voltage					
-					
15.0 amperes resistive load single voltage					
15.0 amperes resistive load single voltage  Contact Adjustability:					
15.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point adjustable					
15.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range:					
15.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point pounds per square inch					
15.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point pounds per square inch  Contact Adjustment Type:					
15.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point pounds per square inch  Contact Adjustment Type:  External actuation point dial					
15.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point pounds per square inch  Contact Adjustment Type:  External actuation point dial  Contact Voltage Rating In Volts:					
15.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point pounds per square inch  Contact Adjustment Type:  External actuation point dial  Contact Voltage Rating In Volts: 250.0 ac at sea level single voltage					
15.0 amperes resistive load single voltage  Contact Adjustability: Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point pounds per square inch  Contact Adjustment Type: External actuation point dial  Contact Voltage Rating In Volts: 250.0 ac at sea level single voltage  Pressure Connector Type:					
15.0 amperes resistive load single voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point pounds per square inch  Contact Adjustment Type:  External actuation point dial  Contact Voltage Rating In Volts: 250.0 ac at sea level single voltage  Pressure Connector Type:  Inverted flare, threaded external single connection					
15.0 amperes resistive load single voltage  Contact Adjustability: Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point pounds per square inch  Contact Adjustment Type: External actuation point dial  Contact Voltage Rating In Volts: 250.0 ac at sea level single voltage  Pressure Connector Type: Inverted flare, threaded external single connection  Media For Which Designed:					
15.0 amperes resistive load single voltage  Contact Adjustability: Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point pounds per square inch  Contact Adjustment Type: External actuation point dial  Contact Voltage Rating In Volts: 250.0 ac at sea level single voltage  Pressure Connector Type: Inverted flare, threaded external single connection  Media For Which Designed: Gas or liquid					

## NSN 5930-00-955-9919

Pressure Switch - Page 2 of 2



T	'nr	ead	<b>Series</b>	Design	nator:

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0