NSN 5930-00-955-9921

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-955-9921

| Hole mounted |
|---|
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 3.016 inches |
| Overall Height: |
| 2.500 inches |
| Overall Width: |
| 1.000 inches |
| Case Material: |
| Plastic |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.328 inches |
| Actuator Free Position Height: |
| 1.500 inches |
| Housing Height: |
| 1.750 inches |
| Housing Length: |
| 2.250 inches |
| Housing Width: |
| 1.000 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Maximum Voltage Rating In Volts: |
| 480.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| Between 6.0 ounces and 9.5 ounces |
| Actuator Movement: |
| Between 0.012 pretravel inches and 0.219 overtravel inches and 0.0005 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 250.000 milliamperes resistive dc and 15.000 amperes resistive ac |

3 screw

Terminal Type And Quantity:

NSN 5930-00-955-9921

Sensitive Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0