NSN 5930-00-956-3048

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-956-3048 **Thread Class:** 2a **Body Style: Bushing mount** Hazardous Locations/environmental Protection: Dustproof and oiltight **Overall Length:** 1.150 inches **Overall Height:** 2.000 inches **Overall Width:** 0.590 inches **Bushing Length:** 0.250 inches **Body Length:** 1.150 inches **Body Width:** 0.590 inches **Body Height:** 0.940 inches **Actuator Style:** Rectangular **Actuator Height:** 0.810 inches **Actuator Width:** 0.375 inches **Actuator Position-action Relationship:** Up position momentary and down position momentary and center position momentary **Actuator Color:** White single actuator **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

NSN 5930-00-956-3048

Toggle Switch - Page 2 of 2

Fiig: A053a0



Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc Special Features: Actuator positions two up and two down Thread Series Designator: Uns Terminal Type And Quantity: 12 turret Shelf Life: N/a Unit Of Measure: -- Demilitarization: No