

View Online at <https://aerobasegroup.com/nsn/5930-00-956-3341>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Actuator Style:**

Round

**Actuator Diameter:**

0.330 inches

**Actuator Height:**

0.328 inches

**Actuator Free Position Height:**

0.983 inches

**Housing Length:**

2.312 inches

**Housing Width:**

1.096 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

0.750 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

0.250 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

3 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

6.0 ounces

**Switch Actuating Force:**

40.0 ounces

**Actuator Movement:**

Between 0.093 pretravel inches and 0.218 overtravel inches and 0.036 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

**Special Features:**

Accoodates 4 0.201 in. Diameter mtg holes

**Terminal Type And Quantity:**

12 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0