

View Online at <https://aerobasegroup.com/nsn/5930-00-956-3341>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Actuator Style:

Round

Actuator Diameter:

0.330 inches

Actuator Height:

0.328 inches

Actuator Free Position Height:

0.983 inches

Housing Length:

2.312 inches

Housing Width:

1.096 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

0.750 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

0.250 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

3 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

40.0 ounces

Actuator Movement:

Between 0.093 pretravel inches and 0.218 overtravel inches and 0.036 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

Special Features:

Accoodates 4 0.201 in. Diameter mtg holes

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0