

View Online at <https://aerobasegroup.com/nsn/5930-00-956-8376>

Thread Class:

3b single pressure connection

Thread Length:

0.594 inches single pressure connection

Overall Length:

3.200 inches

Body Diameter:

1.800 inches

Unthreaded Mounting Hole Diameter:

0.196 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 140.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.454 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

4.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable, preset

Contact Adjustment Range:

+17.00/+29.00 actuation point pounds per square inch

Contact Stimulus Rating:

14.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0