

View Online at <https://aerobasegroup.com/nsn/5930-00-957-0974>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.410 inches

**Overall Height:**

1.030 inches

**Overall Width:**

1.030 inches

**Body Diameter:**

1.030 inches

**Bushing Length:**

0.340 inches

**Body Length:**

2.160 inches

**Case Material:**

Metal

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.310 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

108.0 inch-ounces

**Switch Actuating Force:**

Between 144.0 inch-ounces and 300.0 inch-ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 wire lead

**Specification Data:**

81349-mil-s-8805/48 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0