

View Online at <https://aerobasegroup.com/nsn/5930-00-957-2982>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.660 inches

Overall Height:

Between 2.945 inches and 2.970 inches

Overall Width:

1.340 inches

Bushing Length:

Between 0.455 inches and 0.485 inches

Body Length:

1.660 inches

Body Width:

1.340 inches

Body Height:

Between 0.895 inches and 0.925 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.173 inches and 0.203 inches

Actuator Height:

Between 0.860 inches and 0.890 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

12.000 amperes resistive dc and 5.000 amperes inductive dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 5.000 amperes lamp ac

Test Data Document:

81349-mils3950b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0