

View Online at <https://aerobasegroup.com/nsn/5930-00-957-9363>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.248 inches and 0.252 inches

Body Length:

0.530 inches

Body Width:

Between 0.248 inches and 0.250 inches

Body Height:

Between 0.318 inches and 0.322 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.076 inches

Actuator Length:

Between 0.058 inches and 0.062 inches

Actuator Style:

Rectangular

Actuator Width:

Between 0.128 inches and 0.132 inches

Actuator Free Position Height:

0.297 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained single switch unit

Switch Actuating Force:

7.0 ounces

Actuator Movement:

0.015 pretravel inches and 0.005 overtravel inches and 0.003 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 2.500 amperes inductive dc and 3.000 amperes motor dc and 7.500 amperes resistive ac and 7.500 amperes inductive ac and 3.000 amperes motor ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0