

View Online at <https://aerobasegroup.com/nsn/5930-00-957-9363>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.248 inches and 0.252 inches

**Body Length:**

0.530 inches

**Body Width:**

Between 0.248 inches and 0.250 inches

**Body Height:**

Between 0.318 inches and 0.322 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.076 inches

**Actuator Length:**

Between 0.058 inches and 0.062 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

Between 0.128 inches and 0.132 inches

**Actuator Free Position Height:**

0.297 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained single switch unit

**Switch Actuating Force:**

7.0 ounces

**Actuator Movement:**

0.015 pretravel inches and 0.005 overtravel inches and 0.003 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 2.500 amperes inductive dc and 3.000 amperes motor dc and 7.500 amperes resistive ac and 7.500 amperes inductive ac and 3.000 amperes motor ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0