NSN 5930-00-958-0432

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-958-0432 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Humidity resistant and salt spray resistant and vibration resistant **Overall Length:** 2.375 inches **Overall Height:** 2.563 inches **Overall Width:** 0.562 inches **Body Length:** 1.875 inches **Body Width:** 0.562 inches **Body Height:** 2.250 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.812 inches **Actuator Style:** Round **Actuator Diameter:** 0.343 inches **Actuator Height:** 0.500 inches **Actuator Free Position Height:** 0.500 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 30.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:**

Threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 inch-ounces

Switch Actuating Force:

56.0 ounces

NSN 5930-00-958-0432

Sensitive Switch - Page 2 of 2



Actuator Movement:

0.094 pretravel inches and 0.250 overtravel inches and 0.344 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0