

View Online at <https://aerobasegroup.com/nsn/5930-00-958-4158>

Body Style:

Hole mounted

Overall Length:

2.035 inches

Overall Height:

2.770 inches

Overall Width:

0.520 inches

Body Length:

1.660 inches

Body Width:

0.520 inches

Body Height:

2.090 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.812 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

125.0 ac and 250.0 dc

Inclosure Type:

Uninclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Actuator Movement:

0.188 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 100.000 milliamperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac

Test Data Document:

81349-mil-prf-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 tab w/screw

Specification Data:

81349-mil-prf-8805/56 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

Mil-std (military Standard):

Mil-prf-8805 spec.