

View Online at <https://aerobasegroup.com/nsn/5930-00-958-7984>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Case Material:

Metal

Actuator Style:

Roller arm

Actuator Roller Diameter:

Between 0.845 inches and 0.905 inches

Actuator Roller Width:

Between 0.270 inches and 0.330 inches

Housing Height:

Between 3.160 inches and 3.220 inches

Housing Length:

Between 6.030 inches and 6.090 inches

Housing Width:

Between 2.090 inches and 2.150 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

Between 3.365 inches and 3.385 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

Between 1.490 inches and 1.510 inches

Maximum Voltage Rating In Volts:

600.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

18

Thread Size:

0.312 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch unit

Switch Release Force:

4.0 inch-ounces

Switch Actuating Force:

48.0 inch-ounces

Actuator Movement:

Between 15.0 pretravel degrees and 60.0 overtravel degrees and 7.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 10.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0