

View Online at <https://aerobasegroup.com/nsn/5930-00-958-7984>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Case Material:**

Metal

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

Between 0.845 inches and 0.905 inches

**Actuator Roller Width:**

Between 0.270 inches and 0.330 inches

**Housing Height:**

Between 3.160 inches and 3.220 inches

**Housing Length:**

Between 6.030 inches and 6.090 inches

**Housing Width:**

Between 2.090 inches and 2.150 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

Between 3.365 inches and 3.385 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

Between 1.490 inches and 1.510 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 230.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

0.312 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, both positions maintained single switch unit

**Switch Release Force:**

4.0 inch-ounces

**Switch Actuating Force:**

48.0 inch-ounces

**Actuator Movement:**

Between 15.0 pretravel degrees and 60.0 overtravel degrees and 7.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

400.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0