

View Online at <https://aerobasegroup.com/nsn/5930-00-959-0077>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Actuator Style:**

Round

**Actuator Adapter Style:**

Pushbutton

**Housing Length:**

2.460 inches

**Housing Width:**

1.000 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

1.000 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**End Application:**

Missile, air intercept, sidewinder (aim-9), support equipment, b-52 aircraft, helicopter, advance attack, ah-1w, helicopter, uscg search and rescue, hh-60j, helicopter, carrier based asw, sh-60f, spruance class dd (963), shipboard material handling equipment (mhe), helicopter, search and rescue, hh-60h, helicopter, mh-53e, mars class t-afs 1

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

Between 9.0 ounces and 13.0 ounces

**Actuator Movement:**

Between 0.015 pretravel inches and 0.219 overtravel inches and 0.002 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0