

View Online at <https://aerobasegroup.com/nsn/5930-00-959-2873>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

0.875 inches

**Overall Width:**

0.828 inches

**Bushing Length:**

0.312 inches

**Body Length:**

0.875 inches

**Body Width:**

0.828 inches

**Body Height:**

0.812 inches

**Actuator Diameter:**

0.281 inches

**Actuator Height:**

0.188 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

3 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 3.000 amperes motor dc and 5.000 amperes resistive ac

**Test Data Document:**

77751-31f908532-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0