

View Online at <https://aerobasegroup.com/nsn/5930-00-960-4122>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

Between 0.672 inches and 0.704 inches

Body Height:

0.953 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Length:

Between 1.124 inches and 1.144 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 1.157 inches and 1.219 inches

Actuator Roller Diameter:

Between 0.359 inches and 0.391 inches

Actuator Roller Width:

Between 0.140 inches and 0.172 inches

Maximum Voltage Rating In Volts:

125.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

0.2 ounces

Switch Actuating Force:

0.7 ounces

Actuator Movement:

Between 0.350 pretravel inches and 0.031 overtravel inches and 0.047 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0