

View Online at <https://aerobasegroup.com/nsn/5930-00-960-4122>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.940 inches

**Body Width:**

Between 0.672 inches and 0.704 inches

**Body Height:**

0.953 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

**Actuator Length:**

Between 1.124 inches and 1.144 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

Between 1.157 inches and 1.219 inches

**Actuator Roller Diameter:**

Between 0.359 inches and 0.391 inches

**Actuator Roller Width:**

Between 0.140 inches and 0.172 inches

**Maximum Voltage Rating In Volts:**

125.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

0.2 ounces

**Switch Actuating Force:**

0.7 ounces

**Actuator Movement:**

Between 0.350 pretravel inches and 0.031 overtravel inches and 0.047 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0