

View Online at <https://aerobasegroup.com/nsn/5930-00-960-9022>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.625 inches

Overall Height:

0.968 inches

Overall Width:

1.750 inches

Body Diameter:

1.500 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

1.281 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

37.00 pounds per square inch absolute

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Sensing Element Burst Pressure:

40.00 pounds per square inch absolute

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

4.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+14.70/+37.00 actuation point pounds per square inch absolute and +14.70/+37.00 deactuation point pounds per square inch absolute

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

18.00 deactuation point pounds per square inch absolute and 20.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

30.0 dc at sea level first voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0