

View Online at <https://aerobasegroup.com/nsn/5930-00-961-1721>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof and sand proof

Body Diameter:

1.530 inches

Bushing Length:

0.340 inches

Body Length:

1.375 inches

Case Material:

Metal

Actuator Style:

Round, threaded

Actuator Height:

0.900 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

20.0 inch-ounces

Switch Actuating Force:

30.0 inch-ounces

Actuator Movement:

14.0 pretravel degrees and 10.0 overtravel degrees and 3.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc

Special Features:

Shaft actuator is 0.250 in. Diameter with a screwdriver slot 0.047 x 1/16 in. Deep

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0