

View Online at <https://aerobasegroup.com/nsn/5930-00-961-8870>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

2.718 inches

**Overall Height:**

1.000 inches

**Overall Width:**

0.937 inches

**First Flat Length:**

0.312 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.562 inches single actuator

**Nonturn Device Radius:**

0.375 inches at 1: 30 o'clock

**Individual Section Quantity:**

4

**Nonturn Device Type:**

Tab at 1: 30 o'clock

**Operating Temperature Range:**

-25.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section front

**Throw Quantity:**

4 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

150.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, v flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Detent Rotational Torque Range:**

+12.000/+64.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

20.0 milliamperes resistive load ac at sea level

**Precious Material And Location:**

Terminals and contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0