## NSN 5930-00-962-2583

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-962-2583

## **Thread Class:**

3b single pressure connection

### **Inside Diameter:**

0.562 inches single connection

## **Overall Length:**

3.250 inches

## **Body Length:**

2.125 inches

#### **Overall Diameter:**

2.125 inches

## Pressure Switch Type:

Gage

## **Operating Tempurature Rating:**

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

### Mounting Method:

Line

## **Contact Action Stimulus:**

Increase

#### **Proof Pressure:**

50.00 pounds per square inch

## Thread Size:

0.562 inches single pressure connection

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

## Sensing Element Burst Pressure:

700.00 pounds per square inch

## **Terminal Type:**

Connector, receptacle

## **Contact Load Current Rating:**

4.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage

#### Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

## **Contact Stimulus Rating:**

22.00 actuation point pounds per square inch gage and 15.00 deactuation point pounds per square inch gage

## **Contact Voltage Rating In Volts:**

30.0 dc at altitude single voltage

## Pressure Connector Type:

Gasket seal, threaded internal single connection

## Media For Which Designed:

Liquid

#### Style Designator:

Cylindrical

# NSN 5930-00-962-2583

Pressure Switch - Page 2 of 2



**Thread Series Designator:** 

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0