## NSN 5930-00-962-4695

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-962-4695

			4 . 1 . 5
Hazardous I	l ocations/	environmen	tal Protection:

Vibration resistant and dustproof

**Body Length:** 

2.750 inches

**Overall Diameter:** 

0.500 inches

**Longest Vertical Distance Between Mounting Centers:** 

0.750 inches

**Tempurature Sensing Element Type:** 

Internal sensor

**Mounting Method:** 

Bracket and threaded hole

**Features Provided:** 

Hermetically sealed case

Thready Qty Per Inch (tpi):

32 all threaded hole

**Contact Action Stimulus:** 

Increase

**Thread Size:** 

0.138 inches all threaded hole

**Mounting Facility Pattern:** 

Two position in-line

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally open, momentary action

**Terminal Type:** 

Tab, solder lug

**Contact Load Current Rating:** 

5.0 amperes resistive load single voltage

**Contact Adjustability:** 

Actuation point adjustable, preset

**Contact Adjustment Range:** 

-100.00/+300.00 actuation point degrees fahrenheit

**Contact Adjustment Type:** 

External actuation point tongue

**Contact Stimulus Rating:** 

1.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

115.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

**Style Designator:** 

Cylindrical

## NSN 5930-00-962-4695

Thermostatic Switch - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0