NSN 5930-00-962-4695

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-962-4695

			4 . 1 . 5
Hazardous I	l ocations/	environmen	tal Protection:

Vibration resistant and dustproof

Body Length:

2.750 inches

Overall Diameter:

0.500 inches

Longest Vertical Distance Between Mounting Centers:

0.750 inches

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and threaded hole

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

-100.00/+300.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point tongue

Contact Stimulus Rating:

1.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

NSN 5930-00-962-4695

Thermostatic Switch - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0