## NSN 5930-00-962-5741

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-962-5741

**Thread Class:** 

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

**Overall Length:** 

4.407 inches

**Overall Height:** 

1.500 inches

**Overall Width:** 

1.312 inches

First Flat Length:

0.438 inches single actuator

Flat Height:

0.218 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.938 inches single actuator

**Nonturn Device Radius:** 

0.438 inches at 3: 00 o'clock

**Individual Section Quantity:** 

5

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

1 each section front

**Throw Quantity:** 

12 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

15.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 each section

**Switch Actuator Indexing Position Quantity:** 

12 single actuator

**Shaft Type:** 

Round, flatted single actuator

## **NSN 5930-00-962-5741**Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
2.0 amperes resistive load dc at sea level
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0