NSN 5930-00-962-8495

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-962-8495

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

First Flat Length:

0.250 inches single actuator

Flat Height:

0.220 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.560 inches single actuator

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

NSN 5930-00-962-8495 Rotary Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A052b0