

View Online at <https://aerobasegroup.com/nsn/5930-00-963-1311>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

1.844 inches

**Overall Height:**

0.875 inches

**Overall Width:**

0.875 inches

**Body Diameter:**

0.750 inches

**Bushing Length:**

0.874 inches

**Body Length:**

0.360 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.875 inches

**Actuator Height:**

0.219 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc

**Test Data Document:**

80020-412208-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0