

View Online at <https://aerobasegroup.com/nsn/5930-00-963-1316>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

1.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.150 inches

Overall Width:

0.687 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

1.000 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Length:

2.500 inches

Actuator Style:

Leaf

Actuator Width:

0.190 inches

Actuator Free Position Height:

0.750 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

End Application:

Nimitz class cvn, wichita class aor, gallery equipment & food service, forrestal class cv, laundry equipment catapult/arresting gear.

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.5 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

2.5 ounces

Actuator Movement:

Between 0.328 pretravel inches and 0.219 overtravel inches and 0.997 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0