NSN 5930-00-963-1316

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-963-1316

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.150 inches
Overall Width:
0.687 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
1.000 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
2.500 inches
Actuator Style:
Leaf
Actuator Width:
0.190 inches
Actuator Free Position Height:
0.750 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
End Application:
Nimitz class cvn, wichita class aor, gallery equipment & food service, forrestal class cv, laundry equipment catapult/arresting gear.
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit

0.5 ounces

Switch Release Force:

NSN 5930-00-963-1316 Sensitive Switch - Page 2 of 2



Criticality Code Justification:	
Feat	
Switch Actuating Force:	
2.5 ounces	
Actuator Movement:	
Between 0.328 pretravel inches and 0.219 overtravel inches and 0.997 differential inches	
Contact Load Current Rating At Maximum Rated Voltage:	
250.000 milliamperes resistive dc and 15.000 amperes resistive ac	
Special Features:	
Weapon system essential	
Terminal Type And Quantity:	
3 screw	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A053a0	