NSN 5930-00-963-1344

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-963-1344

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.380 inches
Overall Height:
1.170 inches
Overall Width:
1.562 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.357 inches
Actuator Height:
0.520 inches
Actuator Free Position Height:
1.330 inches
Housing Height:
1.170 inches
Housing Length:
3.050 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.664 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.476 inches
Maximum Voltage Rating In Volts:
480.0 ac and 550.0 dc
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
24
Thread Size:
0.190 inches
Nonpile-up Contact Arrangement:
1 two circuit, one position momentary single switch unit
Switch Release Force:
32.0 ounces
Switch Actuating Force:

96.0 ounces

NSN 5930-00-963-1344

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.065 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 10.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0