# NSN 5930-00-963-5956

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-963-5956

## Thread Class:

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

2.563 inches

## **Overall Height:**

1.875 inches

## **Overall Width:**

1.719 inches

## First Flat Length:

0.250 inches single actuator

## Flat Height:

0.216 inches single actuator

## Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

0.938 inches single actuator

## **Nonturn Device Radius:**

0.437 inches at 3: 00 o'clock

## Individual Section Quantity:

1

## Nonturn Device Type:

Tab at 3: 00 o'clock

## **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

## **Pole Quantity:**

1 single section rear

## **Throw Quantity:**

14 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

300.0 highest ac voltage rating at sea level

## Shaft Flat/slot Angular Location:

320.0 degrees from nonturn device single actuator

## Switch Actuator Indexing Position Quantity:

14 single actuator

# NSN 5930-00-963-5956

Rotary Switch - Page 2 of 2



## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section rear

## Switch Actuator Positioning Increment:

20.0 degrees single actuator

## **Detent Rotational Torque Range:**

+2.000/+8.000 inch-pounds single actuator

## Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

70.0 milliamperes resistive load highest ac voltage rating at sea level

#### Style Designator:

Circular wafer, bushing mount

## **Test Data Document:**

81349-mils3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Thread Series Designator:

Unef single mounting facility

## Shelf Life:

N/a

## Unit Of Measure:

--

## **Demilitarization:**

No

Fiig:

A052b0