NSN 5930-00-963-9235

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-963-9235	
Thread Class:	
3b all threaded hole	
Thread Length:	
0.290 inches all threaded hole	
Overall Length:	
2.830 inches	
Outside Diameter:	
0.438 inches single connection	
Body Diameter:	
1.625 inches	
Body Length:	
1.500 inches	
Overall Diameter:	
1.625 inches	
Longest Horizontal Distance Between Mounting Centers:	
0.795 inches	
Longest Vertical Distance Between Mounting Centers:	
0.795 inches	
Pressure Switch Type:	
Absolute	
Mounting Method:	
Base and threaded hole	
Features Provided:	
Electrical box connector	
Thready Qty Per Inch (tpi):	
32 all threaded hole	
Contact Action Stimulus:	
Increase	
Thread Size:	
0.438 inches single pressure connection	
Mounting Facility Pattern:	
Four position rectangular	
Nonpile-up Contact Arrangement:	
1 pole, double throw, one position momentary	
Terminal Type:	
Connector, receptacle	
Contact Load Current Rating:	
5.0 amperes resistive load single voltage and 3.0 amperes inductive load single voltage	

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

26.50 deactuation point pounds per square inch absolute and 2.50 differential point pounds per square inch absolute

NSN 5930-00-963-9235

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 28.0 dc at sea level single voltage Pressure Connector Type: Flared, threaded external single connection Media For Which Designed: Gas Style Designator: Cylindrical Thread Series Designator: Unf single pressure connection Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A048b0