

View Online at <https://aerobasegroup.com/nsn/5930-00-964-2789>

Thread Length:

0.370 inches single pressure connection

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

2.500 inches

Outside Diameter:

0.125 inches single connection

Body Length:

1.270 inches

Overall Diameter:

1.120 inches

Pressure Switch Type:

Absolute

Operating Temperature Rating:

Between -85.0 degrees fahrenheit and 185.0 degrees fahrenheit

Mounting Method:

Line

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

125.00 pounds per square inch absolute

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

29.00 actuation point pounds per square inch absolute and 26.00 deactuation point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0