

View Online at <https://aerobasegroup.com/nsn/5930-00-964-4949>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant and moisture resistant

**Overall Length:**

1.810 inches

**Overall Height:**

0.625 inches

**Overall Width:**

0.625 inches

**Body Diameter:**

0.625 inches

**Bushing Length:**

0.310 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.325 inches

**Actuator Height:**

0.390 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac

**Test Data Document:**

13499-266-6810-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0