# NSN 5930-00-964-9297

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-964-9297

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.380 inches single mounting facility

## **Overall Length:**

1.818 inches

### **Overall Height:**

1.310 inches

#### **Overall Width:**

1.120 inches

#### First Flat Length:

0.380 inches single actuator

### Flat Height:

0.218 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

# Shaft Length:

0.438 inches single actuator

## Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

6 each section front

### **Throw Quantity:**

2 each section front

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.375 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

2 single actuator

### Shaft Type:

Round, flatted single actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes each section front

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-964-9297

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

1.5 amperes resistive load ac at sea level

#### Precious Material And Location:

Contact surfaces gold

**Precious Material:** 

Gold

# Style Designator:

Square wafer, panel mount

### Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0